Downloaded from UvA-DARE, the institutional repository of the University of Amsterdam (UvA)
http://hdl.handle.net/11245/2.144521

File ID	uvapub:144521
Filename	Contents
Version	final

SOURCE (OR PART OF THE FOLLOWING SOURCE):

Type	PhD thesis
Title	Bose-Einstein condensates in radio-frequency-dressed potentials on an atom chip
Author(s)	J.J.P. van Es
Faculty	FNWI: Van der Waals-Zeeman Institute (WZI)
Year	2009

FULL BIBLIOGRAPHIC DETAILS:
http://hdl.handle.net/11245/1.293016

Copyright

It is not permitted to download or to forward/distribute the text or part of it without the consent of the author(s) and/or copyright holder(s), other than for strictly personal, individual use, unless the work is under an open content licence (like Creative Commons).

UvA-DARE is a service provided by the library of the University of Amsterdam (http://dare.uva.nl)
(pagedate: 2014-11-17)

Contents

1 Introduction **1**
1.1 Historic perspective . . . 1
1.1.1 Conception of Bose-Einstein condensation . . . 2
1.1.2 Technological advances . . . 3
1.2 Cooling and trapping of neutral atoms . . . 4
1.3 Atom chips . . . 5
1.4 The *Celsius* experiment . . . 6
1.5 This thesis . . . 7

2 Theoretical background **9**
2.1 Introduction . . . 9
2.2 Magnetic trapping . . . 9
2.2.1 Basic principles . . . 9
2.2.2 Atom-chip magnetic traps . . . 11
2.2.3 Realistic trapping fields . . . 13
2.3 Radio-frequency dressed potentials . . . 16
2.3.1 The rf-dressed potential . . . 17
2.3.2 RF magnetic field . . . 19
2.3.3 Character of the rf-dressed potential . . . 21
2.4 Electrostatic manipulation . . . 22
2.5 Properties of trapped ultracold gases . . . 23
2.5.1 In-trap longitudinal density distributions . . . 23

3 Atom chip fabrication and characterization **25**
3.1 Introduction . . . 25
3.2 Design considerations . . . 25
3.3 Fabrication protocol . . . 27
3.4 Wire pattern design . . . 30
3.5 Wire characterization . . . 32
3.5.1 Thickness and surface properties . . . 32
3.5.2 Chip wire resistance . . . 34
3.5.3 Inter chip wire resistance . . . 35
3.5.4 Magnetic potential roughness . . . 36
3.5.5 Thermal properties . . . 38
3.5.6 Chip wire breakdown . . . 41
3.6 Summary and conclusion . . . 43

4 Experimental setup **45**
4.1 Introduction . . . 45
4.2 Overview of the experiment . . . 46
4.2.1 Vacuum system . . . 46
4.2.2 Magnetic field coils . . . 47
4.2.3 Lasers . . . 49
4.2.4 Atom chip mount . . . 49
4.2.5 Dispenser . . . 50
4.2.6 Absorption imaging system . . . 51
4.3 Experiment automation . . . 51
4.3.1 Computer control hardware . . . 51
4.3.2 Computer control software . . . 53
4.4 DDS rf generation . . . 57
4.4.1 Introduction . . . 57
4.4.2 Hardware configuration . . . 57
4.4.3 Programming . . . 58
4.4.4 Radio-frequency signal characteristics . . . 62
4.5 Experimental cycle — trapping and cooling sequence . . . 63
4.6 Summary . . . 65

5 Longitudinal character of atom-chip-based rf-dressed potentials **67**
5.1 Introduction . . . 68
5.2 Radio frequency dressed potentials . . . 69
5.3 Experimental setup . . . 71
5.4 Experimental results . . . 73
5.4.1 Effect of magnetic field variations . . . 73
5.4.2 Longitudinal dipole oscillations . . . 76
5.4.3 Beam-splitters for Bose-Einstein condensates . . . 79
5.5 Summary and Conclusion . . . 82

6 Matter-wave interference **85**
6.1 Introduction . . . 85
6.2 Background information . . . 86
6.2.1 Interfering atoms . . . 86
6.2.2 The interference pattern . . . 87
6.2.3 The phase of the macroscopic wave function . . . 88
6.2.4 Properties of the double-well potential . . . 89
6.3 Experimental optimization . . . 90
6.3.1 General procedure . . . 90
6.3.2 Bare-trap dynamics after switch-off of the rf dressing . . . 91
6.3.3 Spin distribution . . . 93
6.4 Matter-wave interference . . . 95
6.5 Summary and outlook . . . 101

A The rf-dressed potential **103**

References **106**

Summary **123**

Samenvatting **125**

Dankwoord **129**

Publication list **131**